



ALUMINUM BODY

MAXIMUM O.A.H. 126.00"

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- KUSSMAUL BATTERY CHARGER LOCATED IN EMS COMPARTMENT
- SUB-FEED CIRCUIT BREAKER PANEL IN COMPARTMENT D3
- ONE L.E.D. LIGHT STRIP LOCATED ON EACH SIDE IN THE HOSEBED
- ONE ADJUSTABLE FULL WIDTH/FULL DEPTH SHELF IN COMPARTMENTS P1,P3, TWO IN D3
- ONE ADJUSTABLE TILTING SLIDE-OUT TRAY IN COMPARTMENTS P1,P2,P3
- ONE FLOOR MOUNTED SLIDE-OUT TRAY WITH 2.00" SIDES AND 500 LB CAPACITY IN COMPARTMENT R1
- ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENTS P1,P3
- THREE SLIDE-OUT ALUMINUM TOOL BOARDS IN COMPARTMENT D1
- ONE VERTICAL PARTITION IN LOCATED IN THE DRIVER'S SIDE HATCH COMPARTMENT, TWO IN THE PASSENGER'S SIDE
- HORIZONTAL EQUIPMENT MOUNTING TRACKS IN COMPARTMENT D2

- CIRCUIT BREAKER PANEL IN COMPARTMENT D3
- ONE 120V DUPLEX RECEPTACLE LOCATED IN EACH EMS COMPARTMENT
- ONE AIR OUTLET W/SHUTOFF VALVE AND MILTON FITTING LOCATED ON D.S. PUMP PANEL
- ONE HANNAY ELECTRIC REWIND AIR REEL MODEL E1514-17-18 WITH 150' OF AIR HOSE LOCATED IN HATCH OVER COMPARTMENTS P3

CUSTOMER APPROVAL			
APPROVED BY:			
DATE:			
REV	DATE	BY	CH
			ENFORCER

Pierce MANUFACTURING INC.

TITLE: 1500-D-1000P W/20G FOAM, 189", FULL HEIGHT & DEPTH, PUC (3) X-LAYS, DELUGE, GENERATOR, REELS

FOR: TROY FIRE DEPARTMENT, TROY, MICHIGAN

DWG NO. 29518AD

JOB NO.	29518
SCALE	1:24
DATE	
DRAWN BY	JWO
CHECKED BY	KBO
SHEET SIZE	D
SHEET NO.	1 OF 1