



ALUMINUM BODY    MAXIMUM O.A.L. 473.00"    MAXIMUM O.A.H. 141.00"    SIDE ROLL & FRONTAL IMPACT PROTECTION

**NOTE**  
DIMENSIONS SHOWN ARE APPROXIMATE  
AND ARE SUBJECT TO MINOR DEVIATIONS  
AS MAY OCCUR OR BE NECESSARY IN  
CONSTRUCTION.  
MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER LOCATED IN COMPARTMENT D3
- BATTERY CHARGE INDICATOR LOCATED ON DRIVER'S SEAT RISER
- AIR INLET WITH DISCONNECT COUPLING LOCATED IN DRIVER'S SIDE CAB STEP WELL
- ONE 120V 6-PLACE RECEPTACLE LOCATED IN CAB AND COMPARTMENT D1
- ONE 120V DUPLEX RECEPTACLE LOCATED IN COMPARTMENT P1
- TWO ADJUSTABLE FULL WIDTH/FULL DEPTH SHELF IN COMPARTMENTS D1, D3, P1, P2, P3, P4
- ONE FLOOR MOUNTED SLIDE-OUT TRAY WITH 500 LB CAPACITY IN COMPARTMENTS D1, D3, P3, P4
- ONE FLOOR MOUNTED SLIDE-OUT TRAY (3 SLIDES) WITH 500 LB CAPACITY IN COMPARTMENT P1
- BREATHING AIR TO AERIAL TIP
- TRIDENT FOLDING STEPS MOUNTED ON AERIAL DEVICE PER SHOP ORDER
- FIRE RESEARCH 3-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP, PUMP PANEL & TURNABLE
- L.E.D. LIGHTING ON AERIAL LADDER SECTIONS
- SPREADER BAR FOR LIFTING EYE RESCUE ATTACHMENT AT AERIAL TIP
- 1500 GPM HIGH FLOW WATERWAY
- COLD CLIMATE PACKAGE
- ONE SHARP VISION CAMERA LOCATED AT EACH SIDE OF AERIAL EGRESS
- REMOTE LADDER CONTROLS AT AERIAL TIP
- ADDITIONAL 54" L.E.D. LIGHT STRIP IN COMPARTMENT D4

REV	DATE	BY	CH	ENFORCER
19JUL16	SHU	COR		
15JUN16	SHU	COR		
12MAY16	SHU	CR1		

		JOB NO.	29865
		SCALE	DATE
TITLE	107' ASCENDANT HSL AERIAL LADDER AND BODY ASSEMBLY 500 GALLON TANK - 470 WATER/30 FOAM	DRAWN BY	SHU
FOR	WOODHAVEN FIRE DEPARTMENT WOODHAVEN, MI	CHECKED BY	CR1
DWG NO.	29865AD	SHEET SIZE	SHEET NO.
		D	1 OF 1